## **AMENDMENTS TO THE CLAIMS**

Please replace the claims, including all prior versions, with the listing of claims below.

## **Listing of Claims:**

1. (Currently Amended) A contact piece of a contact arrangement for the purpose of interrupting a current in a distribution system, comprising: having

a contact carrier-(8) which has a hollow-cylindrical wall section-(9) and a base wall-(10); and

having a contact disk (1) which lies opposite the base wall (10) in a longitudinal direction, slots (2) being provided for the purpose of producing a magnetic field, wherein characterized in that

the rims of the slots-(2) have rounded-off edges (3) having a defined radius.

2. (Currently Amended) The contact piece as claimed in claim 1, characterized in thatwherein

the radius R is set as a function of the <u>a</u>voltage of the distribution system U in accordance with the <u>a</u>rule on dimensions:

$$R \ge 2 \cdot 10^{-4} \cdot U^2 + 8.5 \cdot 10^{-3} \cdot U + 0.34$$
,

where U has the a unit kilovolts and R has the a unit millimeters.

- 3. (Currently Amended) The contact piece as claimed in claim 1-or-2, eharacterized in that wherein the slots-(2) have slot ends-(4) in thea form of a rounded hole (5, 6).
- 4. (Currently Amended) The contact piece as claimed in claim 3, eharacterized in that wherein the diameter of the rounded hole (6)-is in thea region of a slot width of the slots-(2).

- (Currently Amended) The contact piece as claimed in either of claims 1 and 2, 5. characterized in that claim 1, wherein the slots (2) have rectangular slot ends (7).
- 6. (Currently Amended) The contact piece as claimed in one of the preceding claims, characterized in that claim 1, wherein the slots-(2) are provided in the wall section-(9) and are inclined with respect to the a longitudinal direction.
- 7. (Currently Amended) The contact piece as claimed in one of the preceding claims, characterized in that claim 1, wherein the slots (2)-are formed in the contact disk-(1).
- 8. (Currently Amended) The contact piece as claimed in-one of the preceding claims, characterized in that claim 1, wherein the slots (2) are provided in the base wall (10).